

It includes a built-in amplifier and speaker. A flexible gooseneck microphone. A number of input and output connections make it easy to expand its capacity. Available in smart and rebust design with black finish. Built-in 60W Speaker
Flexible gooseneck MIC's Available.



90 Watt

Technical Specifications

Power Output	90 Watts
Input Channels	Mic-1 (Gooseneck Mic) 8mV, Mic-2 : 4mV, Line-100mV, AUX-200mV
Frequency Response	50 - 16,000Hz
Tone Control	Bass ± 5 dB at 100Hz, Treble ± 5 dB at 10k Hz
MIX Output	775mV
Digital Player	MP3 Recorded Player with USB, SD, MMC Card & Bluetooth
USB Charger Outlet	DC-5V, 1A
External Speaker Impedance	4 Ω to 8 Ω
Power Supply	AC 220-240V, 50/60Hz
Power Consumption	AC 100VA
Dimensions	L580 x W420 x H1100 mm
Weight	30 kg
Microphone	Handheld Transmitter
Microphone Element	Dynamic, Cardioid
Transmission Distance	15-30 Meters
RF Output Power	15mW
Frequency Response	50 - 15,000Hz
Power Requirement	3V (2x1.5V AA Pencil Cells)
Current Consumption	< 100 mA
Weight (w/o Battery)	180 gm



Marketed & Distributed by :

RAMESHWARAM TECHNOLOGY

📍 Sangam Vihar, Dharampura, Najafgarh, Delhi - 110043

☎ +91 9625259502

🌐 www.rameshwaramtech.in

✉ rameshwaramtechnology@gmail.com

All India Services

